

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 1

Compilation date: 02/09/2019

Revision No: 3

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION - ACTIVATOR

Product code: M-CERAM 401

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Maxkote Limited

Tower Court, Oakdale Road
Clifton Moor
Yorks
North Yorkshire
YO30 4XL
United Kingdom

Tel: 01904 809 773

Email: info@MaxKote.co.uk

1.4. Emergency telephone number

Emergency tel: 01904 809773

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: C: R34; Sens.: R43; -: R52/53; Xn: R62

Classification under CLP: Aquatic Chronic 3: H412; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1A: H317

Most important adverse effects: Causes burns. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

H317: May cause an allergic skin reaction.

H361f: Suspected of damaging fertility.

H412: Harmful to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS08: Health hazard

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 2



Precautionary statements: P102: Keep out of reach of children.
P202: Do not handle until all safety precautions have been read and understood.
P260: Do not breathe vapours.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P302+352: IF ON SKIN: Wash with plenty of water/.
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333+313: If skin irritation or rash occurs: Get medical advice/attention.
P501: Dispose of contents/container to hazardous or special waste collection point.

Label elements under CHIP:

Hazard symbols: Corrosive.



Risk phrases: R34: Causes burns.
R43: May cause sensitisation by skin contact.
R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R62: Possible risk of impaired fertility.

Safety phrases: S1/2: Keep locked up and out of the reach of children.
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S29: Do not empty into drains.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 3

Hazardous ingredients:

4-TERT-BUTYLPHENOL

EINECS	CAS	CHIP Classification	CLP Classification	Percent
202-679-0	98-54-4	Xi: R38; Xi: R41; Xn: R62	Repr. 2: H361f; Skin Irrit. 2: H315; Eye Dam. 1: H318	10-30%

M-PHENYLENEBIS(METHYLAMINE)

216-032-5	1477-55-0	C: R34; Xn: R20/22; Sens.: R43	Skin Corr. 1B: H314; Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H332	1-10%
-----------	-----------	--------------------------------	--	-------

TRIMETHYLHEXANE-1,6-DIAMINE

247-063-2	25513-64-8	C: R34; Xn: R22; Sens.: R43	Skin Corr. 1C: H314; Acute Tox. 4: H302; Skin Sens. 1A: H317; Aquatic Chronic 3: H412; Acute Tox. 4: H312	1-10%
-----------	------------	-----------------------------	---	-------

PHENOL, STYROLISED

262-975-0	61788-44-1	Xi: R38; Sens.: R43; N: R51/53	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-10%
-----------	------------	--------------------------------	--	-------

BENZYL ALCOHOL

202-859-9	100-51-6	Xn: R20/22	Acute Tox. 4: H332; Acute Tox. 4: H302	1-10%
-----------	----------	------------	--	-------

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

217-168-8	1761-71-3	-	Acute Tox. 4: H302; Skin Sens. 1: H317; STOT RE 2: H373; Skin Corr. 1B: H314	1-10%
-----------	-----------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10 minutes. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 4

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Notify the police and fire brigade immediately. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 5

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.
Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency. Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Paste

Colour: Dark grey

Odour: Ammoniacal

Solubility in water: Insoluble

Viscosity: Non-viscous

Boiling point/range°C: >200

Flash point°C: >100

Autoflammability°C: 380

Relative density: 1.4

9.2. Other information

Other information: No data available.

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 6

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

DERMAL	RAT	LD50	3100	mg/kg
ORAL	RAT	LD50	930	mg/kg

TRIMETHYLHEXANE-1,6-DIAMINE

DERMAL	RAT	LD50	1280	mg/kg
ORAL	RAT	LD50	910	mg/kg

PHENOL, STYROLISED

DERMAL	RAT	LD50	>2000	mg/kg
ORAL	RAT	LD50	>2000	mg/kg

BENZYL ALCOHOL

IVN	RAT	LD50	53	mg/kg
ORL	MUS	LD50	1360	mg/kg

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 7

ORL	RAT	LD50	1230	mg/kg
-----	-----	------	------	-------

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

DERMAL	RBT	LD50	2110	mg/kg
ORAL	RAT	LD50	625	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Corrosivity	OPT INH DRM	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated
Toxicity for reproduction	--	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

M-PHENYLENEBIS(METHYLAMINE)

DAPHNIA	48H EC50	15.2	mg/l
FISH	96H LC50	>100	mg/l

TRIMETHYLHEXANE-1,6-DIAMINE

FISH	48H EC50	174	mg/l
------	----------	-----	------

PHENOL, STYROLISED

DAPHNIA	48H EC50	1-10	mg/l
FISH	96H LC50	14.8	mg/l

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 8

4,4-METHYLENEBIS(CYCLOHEXYLAMINE)

Daphnia magna	48H EC50	6.84	mg/l
---------------	----------	------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1759

14.2. UN proper shipping name

Shipping name: CORROSIVE SOLID, N.O.S.
(4-TERT-BUTYLPHENOL)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: II

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: Yes

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 9

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H332: Harmful if inhaled.
H361f: Suspected of damaging fertility.
H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.
R20/22: Harmful by inhalation and if swallowed.
R22: Harmful if swallowed.
R34: Causes burns.
R38: Irritating to skin.
R41: Risk of serious damage to eyes.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

[cont...]

SAFETY DATA SHEET

M-CERAM 401 EPOXY CERAMIC WEAR COMPOUND HIGH ABRASION
ACTIVATOR

Page: 10

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R62: Possible risk of impaired fertility.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.