

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name M-CORR 400 UV STABLE POLYURETHANE TOP COAT - ACTIVATOR

Product number M-CORR 400

1.2. Relevant identified uses of the substance or mixture and uses advised against Identified uses

Paint.

1.3. Details of the supplier of the safety data sheet

Supplier MaxKote Ltd
Tower Court, Oakdale Road
Clifton Moor
York
YO30 4XL
North Yorkshire

Tel: 01904 809 773

info@maxkote.co.uk

Emergency telephone 01904 809 773

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Elicitation - EUH208 Elicitation - EUH208

Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xn;R20/21. R10.

Human health Vapours and spray/mists in high concentrations are narcotic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Harmful by inhalation and in contact with skin. The liquid may be irritating to skin.

Environmental The product is not expected to be hazardous to the environment.

Physicochemical The product is flammable. Heating may generate flammable vapours.

2.2. Label elements

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

Pictogram



Signal word

Warning

Hazard statements

EUH208 Contains HEXAMETHYLENE-DI-ISOCYANATE. May produce an allergic reaction.
H226 Flammable liquid and vapour.
H315 Causes skin irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P302+P352 IF ON SKIN: Wash with plenty of water.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/ container in accordance with national regulations.

Supplementary precautionary statements

P233 Keep container tightly closed.
P240 Ground/ bond container and receiving equipment.
P241 Use explosion-proof electrical equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P264 Wash contaminated skin thoroughly after handling.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

XYLENE	10-30%
CAS number: 1330-20-7	EC number: 215-535-7
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	R10 Xn;R20/21 Xi;R38
Acute Tox. 4 - H312	
Acute Tox. 4 - H332	
Skin Irrit. 2 - H315	
Asp. Tox. 1 - H304	
2-METHOXY-1-METHYLETHYL ACETATE	10-30%
CAS number: 108-65-6	EC number: 203-603-9
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 3 - H226	R10 Xi;R36

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

BUTYL ACETATE -norm CAS number: 123-86-4 EC number: 204-658-1	5-10%
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336	Classification (67/548/EEC or 1999/45/EC) R10 R66 R67
ETHYLBENZENE CAS number: 100-41-4 EC number: 202-849-4	1-5%
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) F;R11 Xn;R20
HEXAMETHYLENE-DI-ISOCYANATE CAS number: 822-06-0 EC number: 212-485-8	<1%
Classification Acute Tox. 3 - H331 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Resp. Sens. 1 - H334 Skin Sens. 1 - H317 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) T;R23 R42/43 Xi;R36/37/38

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Composition comments The data shown are in accordance with the latest EC Directives.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Never give anything by mouth to an unconscious person. Get medical attention if any discomfort continues.
Inhalation	Place unconscious person on their side in the recovery position and ensure breathing can take place. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
Skin contact	Immediately remove contaminated clothing. Rinse immediately with plenty of water.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention promptly if symptoms occur after washing.

4.2. Most important symptoms and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Water spray, fog or mist. Foam, carbon dioxide or dry powder. Dry chemicals, sand, dolomite etc.

5.2. Special hazards arising from the substance or mixture

Specific hazards Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours.

Hazardous combustion products Carbon monoxide (CO). Carbon dioxide (CO₂). Oxides of nitrogen. Hydrogen cyanide (HCN).

5.3. Advice for firefighters

Protective actions during firefighting Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Cool containers exposed to flames with water until well after the fire is out.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Keep combustible materials away from spillage. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Wash thoroughly after dealing with a spillage.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Keep away from oxidising materials, heat and flames. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Avoid contact with oxidising agents. Contents may develop pressure upon prolonged storage.

Storage class Flammable liquid storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)
Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)
Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³
Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)
Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

HEXAMETHYLENE-DI-ISOCYANATE

Long-term exposure limit (8-hour TWA): WEL 0.02 mg/m³(Sen)
Short-term exposure limit (15-minute): WEL 0.07 mg/m³(Sen)
WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used. Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients. Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. All handling should only take place in well-ventilated areas.

Eye/face protection

Wear chemical splash goggles.

Hand protection

Wear protective gloves made of the following material: Neoprene. Nitrile rubber. Rubber (natural, latex).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Provide eyewash station. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

Respiratory protection

Air-fed protective respiratory equipment must be worn by the spray operator, even when good ventilation is provided. For non-spraying application, in well ventilated areas, air-fed respirators can be replaced by a respirator with the following cartridge: Organic vapour filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Clear.
Odour	Organic solvents.
Odour threshold	Not determined.

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

pH	Not available.
Initial boiling point and range	124°C
Flash point	38°C
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.1% Upper flammable/explosive limit: 7.6%

Relative density	1.03 - 1.04
Solubility(ies)	Not available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 380 g/l.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No test data specifically related to reactivity available for this product or its ingredients.

10.2. Chemical stability

Stability No particular stability concerns.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Reaction with water forms CO₂ which can cause pressure build up in closed containers.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Oxidising agents. Strong alkalis. Strong acids. Amines. Alcohols. Water, moisture.

10.6. Hazardous decomposition products

Hazardous decomposition products Oxides of carbon. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - dermal

ATE dermal (mg/kg) 7,187.52

Acute toxicity - inhalation

ATE inhalation (gases ppm) 22,102.81

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

ATE inhalation (vapours mg/l) 56.63

ATE inhalation (dusts/mists
mg/l) 7.81

General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing. Harmful by inhalation.
Ingestion	Gastrointestinal symptoms, including upset stomach.
Skin contact	Product has a defatting effect on skin. May cause allergic contact eczema. Irritating to skin. Harmful in contact with skin.
Eye contact	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain.

SECTION 12: Ecological Information

Ecotoxicity The product is not expected to be hazardous to the environment.

12.1. Toxicity

12.2. Persistence and degradability

Persistence and degradability No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential Expected to be low.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility No data available.

12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB
assessment** This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste should be treated as controlled waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Absorb in vermiculite, dry sand or earth and place into containers. Dispose of waste via a licensed waste disposal contractor.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1263

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ADN packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant
No.

14.6. Special precautions for user

EmS F-E, S-E

Hazard Identification Number 33
(ADR/RID)

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

M-CORR 400 UV STABLE POLYURETHANE TOP COAT ACTIVATOR

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716). EH40/2005 Workplace exposure limits.
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
Guidance	Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	11/01/2017
Revision	4
Supersedes date	18/11/2015
Risk phrases in full	R10 Flammable. R11 Highly flammable. R20 Harmful by inhalation. R20/21 Harmful by inhalation and in contact with skin. R23 Toxic by inhalation. R36 Irritating to eyes. R36/37/38 Irritating to eyes, respiratory system and skin. R38 Irritating to skin. R42/43 May cause sensitisation by inhalation and skin contact. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
Hazard statements in full	EUH208 Contains HEXAMETHYLENE-DI-ISOCYANATE. May produce an allergic reaction. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H312 Harmful in contact with skin. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H331 Toxic if inhaled. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.