

## SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 1

Compilation date: 19/05/2018

Revision date: 19/05/2018

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name:** RESIFLEX 401 GP 60 PUTTY BASE COMPONENT

**Product code:** 401

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Use of substance / mixture:** PC1: Adhesives, sealants. PC9a: Coatings and paints, thinners, paint removers. PC9b: Fillers, putties, plasters, modelling clay. PC32: Polymer preparations and compounds. PROC1: Use in closed process, no likelihood of exposure PROC2: Use in closed, continuous process with occasional controlled exposure PROC3: Use in closed batch process (synthesis or formulation) PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises PROC5: Mixing or blending in batch processes for formulation of preparations\* and articles (multistage and/or significant contact) PROC8a: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing) PROC10: Roller application or brushing PROC13: Treatment of articles by dipping and pouring PROC19: Hand-mixing with intimate contact and only PPE available ERC2: Formulation of preparations\* ERC3: Formulation in materials ERC5: Industrial use resulting in inclusion into or onto a matrix ERC6d: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

#### 1.3. Details of the supplier of the safety data sheet

**Company name:** Maxkote Ltd

Tower Court, Oakdale Road  
Clifton Moor  
Yorks  
North Yorkshire  
YO30 4XL  
United Kingdom

**Tel:** 01904 809 773

**Email:** [info@MaxKote.co.uk](mailto:info@MaxKote.co.uk)

# SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 2

## 1.4. Emergency telephone number

**Emergency tel:** +44 (0) 1904 809 773  
(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

**Classification under CLP:** Eye Irrit. 2: H319; Aquatic Chronic 2: H411; Skin Sens. 1: H317; STOT RE 2: H373

**Most important adverse effects:** May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Label elements:

**Hazard statements:** H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H411: Toxic to aquatic life with long lasting effects.

**Hazard pictograms:** GHS07: Exclamation mark  
GHS08: Health hazard  
GHS09: Environmental



**Signal words:** Warning

**Precautionary statements:** P260: Do not breathe dust/fumes/gas/mist/vapours/spray.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P314: Get medical attention if you feel unwell.  
P321: Specific treatment (see instructions on this label).

### 2.3. Other hazards

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

**PBT:** This product is not identified as a PBT/vPvB substance.

[cont...]

# SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 3

## Hazardous ingredients:

DIETHYLMETHYLBENZENEDIAMINE - REACH registered number(s): 01-2119486805-25

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-877-4	68479-98-1	-	Acute Tox. 4: H312; Acute Tox. 4: H302; STOT RE 2: H373; Eye Irrit. 2: H319; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	1-25%

4,4'-METHYLENEBIS(N-SEC-BUTYLANILINE)

226-122-6	5285-60-9	-	Acute Tox. 4: H302; Skin Sens. 1: H317; Aquatic Acute 1: H400; Aquatic Chronic 1: H410	1-25%
-----------	-----------	---	--	-------

NEODECANOIC ACID, ZINC SALT

248-370-4	27253-29-8	-	Aquatic Chronic 2: H411	1-25%
-----------	------------	---	-------------------------	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Move to fresh air in case of accidental inhalation of vapours. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Immediate / special treatment:** Show this safety data sheet to the doctor in attendance.

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

[cont...]

# SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 4

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear protective clothing to prevent contact with skin and eyes. Wear self-contained breathing apparatus.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

### 6.3. Methods and material for containment and cleaning up

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Mix with sand or vermiculite. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Clean-up should be dealt with only by qualified personnel familiar with the specific substance.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS. Refer to section 13 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Keep container tightly closed. Avoid contact with water or humidity.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Specific end use(s):** No data available.

**Workplace exposure limits:** No data available.

### DNEL/PNEC Values

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 5

## DIETHYLMETHYLBENZENEDIAMINE

Type	Exposure	Value	Population	Effect
DNEL	Dermal (repeated dose)	1 mg/kg	Workers	Systemic
DNEL	Inhalation (repeated dose)	0.13 mg/kg	Workers	Systemic
PNEC	Fresh water	0.0005 mg/l	-	-
PNEC	Fresh water sediments	0.029 mg/kg	-	-
PNEC	Marine water	0.00005 mg/l	-	-
PNEC	Marine sediments	0.0029 mg/kg	-	-
PNEC	Soil (agricultural)	0.0056 mg/kg	-	-
PNEC	Microorganisms in sewage treatment	17 mg/l	-	-

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141). Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Environmental:** Ensure all engineering measures mentioned in section 7 of SDS are in place.

### Section 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

**State:** Paste

**Colour:** Black

**Odour:** Characteristic odour

**Evaporation rate:** No data available.

**Oxidising:** No data available.

**Solubility in water:** No data available.

**Viscosity:** Highly viscous

**Boiling point/range°C:** No data available.

**Flammability limits %: lower:** No data available.

**Flash point°C:** No data available.

**Autoflammability°C:** No data available.

**Relative density:** 1.04 - 1.08

**VOC g/l:** No data available.

**Melting point/range°C:** No data available.

**upper:** No data available.

**Part.coeff. n-octanol/water:** No data available.

**Vapour pressure:** No data available.

**pH:** No data available.

#### 9.2. Other information

**Other information:** No data available.

[cont...]

# SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 6

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

### 10.3. Possibility of hazardous reactions

**Chemical stability:** Stable under normal conditions.

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat. Moist air. Humidity.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

**Materials to avoid:** Water. Acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### DIETHYLMETHYLBENZENEDIAMINE

DERMAL	RAT	LD50	>2000	mg/kg
ORL	RAT	LD50	738	mg/kg

#### 4,4'-METHYLENEBIS(N-SEC-BUTYLANILINE)

DERMAL	RBT	LD50	3090	mg/kg
ORAL	RAT	LD50	1380	mg/kg

#### Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-repeated exposure	-	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness.

**Ingestion:** Nausea and stomach pain may occur.

**Inhalation:** There may be a feeling of tightness in the chest with shortness of breath. Exposure may

cause coughing or wheezing.

[cont...]

# SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 7

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Hazardous ingredients:**

#### DIETHYLMETHYLBENZENEDIAMINE

Daphnia magna	48H EC50	0.5	mg/l
FATHEAD MINNOW (Pimephales promelas)	96H LC50	>106	mg/l
GOLDEN ORFE (Leuciscus idus)	48H LC50	200	mg/l
GREEN ALGAE (Desmodesmus subspicatus)	72H ErC50	104	mg/l

### 12.2. Persistence and degradability

**Persistence and degradability:** No data available.

### 12.3. Bioaccumulative potential

### 12.4. Mobility in soil

**Bioaccumulative potential:** No data available.

**Mobility:** No data available.

### 12.5. Results of PBT and vPvB assessment

### 12.6. Other adverse effects

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**Other adverse effects:** No data available.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**Disposal of packaging:** Arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3082

### 14.2. UN proper shipping name

**Shipping name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(Contains: DIETHYLMETHYLBENZENEDIAMINE)

[cont...]

## SAFETY DATA SHEET

M-RUBBER 100 ELASTOMER  
REPAIR PUTTY - BASE

Page: 8

### 14.3. Transport hazard class(es)

Transport class: 9

### 14.4. Packing group

### 14.5. Environmental hazards

Packing group: III

Environmentally hazardous: Yes

Marine pollutant: Yes

### 14.6. Special precautions for user

Tunnel code: E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

Specific regulations: Not applicable.

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H373: May cause damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H400: Very toxic to aquatic life.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.